Safety Data Sheet MAPEPROOF ESM parte B

Safety Data Sheet dated: 21/07/2022 - version 1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MAPEPROOF ESM parte B

Trade code: 9024202 UFI: CF90-M0F6-C006-EN4A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Hardener for epoxy products

Uses advised against: Not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification







2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Acute Tox. 4 Harmful if swallowed.

Skin Corr. 1A Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1 May cause an allergic skin reaction.

STOT RE 2 May cause damage to organs through prolonged or repeated exposure.

Aguatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Danger

Hazard statements:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 1 of 15

P310 Immediately call a POISON CENTER.

Special Provisions:

EUH208 Contains triethylenetetramine. May produce an allergic reaction.

EUH208 Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine. May produce an allergic reaction.

EUH208 Contains 2-piperazin-1-ylethylamine. May produce an allergic reaction.

Contains:

Reaction products of 3-aminomethyl-3,5,5-trimethylcyclohexylamine and 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane

benzyl alcohol

2,4,6-tris(dimethylaminomethyl)phenol

benzyl alcohol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

PBT, vPvB or endocrine disruptor substances present in concentration >= 0,1%:

Component Ident. Numb. Quantity Properties:

4-tert- CAS: 98-54-4 - EINECS: 202-679-0 - 67-548-EC: >=1 - <2.5 % SVHC - Endocrine disruptor

butylphenol 604-090-00-8

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: MAPEPROOF ESM parte B

Hazardous components within the meaning of the CLP regulation and related classification:

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number	Properties :
≥25 - <50 %	Reaction products of 3- aminomethyl-3,5,5- trimethylcyclohexylamine and 4,4' Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane		Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412		
≥20 - <25 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057- 00-5	Acute Tox. 4, H302; Acute Tox. 4, H332	01-2119492630-38- XXXX	
≥10 - <20 %	2,4,6- tris(dimethylaminomethyl)phenol	CAS:90-72-2 EC:202-013-9 Index:603-069- 00-0	Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	01-2119560597-27- XXXX	
≥5 - <10 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057- 00-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Eye Irrit. 2, H319	01-2119492630-38- XXXX	
≥5 - <10 %	2-Methylpentane-1,5-diamine	CAS:15520-10-2 EC:239-556-6	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Corr. 1A, H314; Eye Dam. 1, H318; STOT SE 3, H335	01-2119976310-41- XXXX	
≥5 - <10 %	triethylenetetramine	CAS:90640-67- 8, 112-24-3 EC:292-588-2	Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071		

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 2 of 15

≥2.5 - <5 %	3-aminomethyl-3,5,5- trimethylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067- 00-9	Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412	01-2119514687-32- xxxx	
≥1 - <2.5 %	2-piperazin-1-ylethylamine	CAS:140-31-8 EC:205-411-0 Index:612-105- 00-4	Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Acute Tox. 4, H302; Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412	01-2119471486-30	
≥1 - <2.5 %	4-tert-butylphenol	CAS:98-54-4 EC:202-679-0 Index:604-090- 00-8	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 1, H410; Repr. 2, H361f, M-Chronic:1	01-2119489419-21- XXXX	SVHC Endocrine disruptor

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Give nothing to eat or drink.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 3 of 15

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

,	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Note
benzyl alcohol CAS: 100-51-6	NDS			240		,		
	Nationa	FINLAND		45	10			
	DFG	GERMANY	С			44	10	
	Nationa	GERMANY		22	5			
	NDS	POLAND		240				
	Nationa	CZECH REPUBLIC		40				
	Nationa	LATVIA		5				
	Nationa	CZECH REPUBLIC	С			80		
	Nationa	BULGARIA		5.0				
	Nationa	LITHUANIA		5				
	Nationa	SLOVENIA		22	5	44	10	
benzyl alcohol CAS: 100-51-6	Nationa	FINLAND		45	10			
	Nationa	POLAND		240				
	DFG	GERMANY	С			44	10	
	Nationa	GERMANY		22	5			
	NDS	POLAND		240				
	Nationa	CZECH REPUBLIC		40				
	Nationa	I LATVIA		5				
	Nationa	CZECH REPUBLIC	С			80		
	Nationa	BULGARIA		5.0				
	Nationa	LITHUANIA		5				
	Nationa	SLOVENIA		22	5	44	10	
4-tert-butylphenol	DFG	GERMANY	С			1.0	0.16	
Print date	23/07/2022	Production	n Name	MAPEPI	ROOF ESM	parte B		

Page n. 4 of 15
 National DENMARK
 0.5
 0.08

 National GERMANY
 0.5
 0.08

 CHE SWITZERLAND
 1
 0.16

 National SLOVENIA
 0.5
 0.08
 2
 0.32

 National SLOVAKIA
 0.08
 0.08
 2
 0.32

	National SLOVAKIA		0.08
Predicted No Effect Cor	ncentration (PNEC) values		
	PNEC Limit	Exposure Route	Exposure Frequency Remark
Reaction products of 3-aminomethyl-3,5,5-trimethylcyclohexylamine and 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane CAS: 38294-64-3, 68609-08-5		Fresh Water	
		Marine water	
		Intermittent release	
	10 mg/l	Microorganisms in sewage treatments	
		Freshwater sediments	
		Marine water sediments	
		Soil	
	1 mg/kg	Oral	
benzyl alcohol CAS: 100-51-6	1 mg/l	Fresh Water	
	0.1 mg/l	Marine water	
	5.27 mg/kg	Freshwater sediments	
	0.527 mg/kg	Marine water sediments	
	39 mg/l	Microorganisms in sewage treatments	
	0.45 mg/kg	Soil	
	2.3 mg/l	Intermittent release	
2-Methylpentane-1,5-	0.042 mg/l	Marine water	
diamine CAS: 15520-10-2			
	0.42 mg/l	Fresh Water	
	0.42 mg/l	Intermittent release	
triethylenetetramine CAS: 90640-67-8, 112- 24-3	0.123 mg/kg	Marine water sediments	
	2.08 mg/kg	Freshwater sediments	
	8 mg/l	Microorganisms in sewage treatments	
3-aminomethyl-3,5,5- trimethylcyclohexylamine CAS: 2855-13-2	0.06 mg/l	Fresh Water	

0.006 mg/l Marine water

0.23 mg/l Intermittent release

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 5 of 15

5.784 Freshwater mg/kg sediments 0.578 Marine water sediments mg/kg 1.121 Soil mg/kg 3.18 mg/l Microorganisms in sewage treatments 0.058 mg/l Fresh Water 0.0058 Marine water mg/l 0.58 mg/l Intermittent release 215 mg/kg Freshwater sediments

21.5 mg/kg Marine water

42.9 mg/kg Soil

2-piperazin-1ylethylamine CAS: 140-31-8

250 mg/l Microorganisms in sewage treatments

sediments

Derived No Effect Level. (DNEL)						
	Worker Worke Industr Profes y ional		Exposure Route	Exposure Frequency Remark		
Reaction products of 3- aminomethyl-3,5,5- trimethylcyclohexylamine and 4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane CAS: 38294-64-3, 68609 08-5		0.74 mg/m3	Human Inhalation	Long Term, systemic effects		
	0.14 mg/kg	0.05 mg/kg	Human Dermal	Long Term, systemic effects		
			Human Oral	Long Term, systemic effects		
2,4,6- tris (dimethylaminomethyl) phenol CAS: 90-72-2	0.31 mg/m3		Human Inhalation	Long Term, systemic effects		
benzyl alcohol CAS: 100-51-6		20 mg/kg	Human Oral	Short Term, systemic effects		
		4 mg/kg	Human Oral	Long Term, systemic effects		
	110 mg/m3	27 mg/m3	Human Inhalation	Short Term, systemic effects		
	22 mg/m3	5.4 mg/m3	Human Inhalation	Long Term, systemic effects		
	40 mg/kg	20 mg/kg	Human Dermal	Short Term, systemic effects		
	8 mg/kg	4 mg/kg	Human Dermal	Long Term, systemic effects		
2-Methylpentane-1,5- diamine CAS: 15520-10-2	1.5 mg/kg		Human Dermal	Long Term (repeated)		

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 6 of 15

	0.25 mg/m3			Human Inhalation	Long Term (repeated)
	0.5 mg/m3			Human Inhalation	Short Term (acute)
triethylenetetramine CAS: 90640-67-8, 112- 24-3		5.38 mg/l		Human Inhalation	Short Term, local effects
		0.57 mg/kg		Human Dermal	Long Term, systemic effects
			20 mg/kg	Human Oral	Short Term, systemic effects
			8 mg/kg	Human Dermal	Short Term, systemic effects
			1.6 mg/l	Human Inhalation	Short Term, systemic effects
3-aminomethyl-3,5,5- trimethylcyclohexylamine CAS: 2855-13-2	20.1 mg/m3			Human Inhalation	
2-piperazin-1- ylethylamine CAS: 140-31-8	20 mg/kg		10 mg/kg	Human Dermal	Short Term, systemic effects
	0.04 mg/cm2		0.02 mg/cm2	Human Dermal	Short Term, local effects
	3.3 mg/kg		1.7 mg/kg	Human Dermal	Long Term, systemic effects
	3.6 mg/m3		0.9 mg/m3	Human Inhalation	Long Term, systemic effects
	0.006 mg/cm2		0.003 mg/cm2	Human Dermal	Long Term, local effects
	21.4 mg/m3		5.3 mg/m3	Human Inhalation	Short Term, systemic effects
			1.5 mg/kg	Human Oral	Short Term, systemic effects
			0.3 mg/kg	Human Oral	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 7 of 15

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: liquid Color: Yellow

Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available Initial boiling point and boiling range: Not available

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: Not available Viscosity: Not available

Kinematic viscosity: Not available Solubility in water: partly soluble

Solubility in oil: soluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: Not available Vapour density: Not available **Particle characteristics:** Particle size: Not available

9.2. Other information

Miscibility: Not available
Conductivity: Not available
Explosive properties: ==
No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the mixture:

a) acute toxicity The product is classified: Acute Tox. 4(H302)

ATEmix - Oral: 1568.33 mg/kg bw

b) skin corrosion/irritation The product is classified: Skin Corr. 1A(H314) c) serious eye damage/irritation The product is classified: Eye Dam. 1(H318) d) respiratory or skin sensitisation The product is classified: Skin Sens. 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 8 of 15

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure The product is classified: STOT RE 2(H373)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Reaction products of 3-

aminomethyl-3,5,5trimethylcyclohexylamine

and 4,4'-

Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane

a) acute toxicity

NOAEL Oral Rat = 30 mg/kg

benzyl alcohol

a) acute toxicity

LC50 Inhalation Rat = 11 mg/l 4h

LD50 Oral Rat = 1230 mg/kg

2,4,6-

a) acute toxicity

LD50 Oral Rat = 2169 mg/kg

tris

(dimethylaminomethyl)

phenol

LD50 Skin Rat > 1 ml/kg

benzyl alcohol

a) acute toxicity

LC50 Inhalation Rat = 11 mg/l 4h

LD50 Oral Rat = 1230 mg/kg

g) reproductive toxicity

NOAEL Rat = 1072 mg/m3

2-Methylpentane-1,5-

diamine

a) acute toxicity

LC50 Inhalation Mist Rat = 4.9 mg/l 1h

LD50 Oral Rat = 1170 mg/kg LD50 Skin Rat = 1870 mg/kg LC50 Inhalation Rat = 4.1 mg/l 1h LC50 Inhalation Rat = 2.9 mg/l 1h LD50 Oral Rat = 1690 mg/kg

triethylenetetramine

a) acute toxicity

LD50 Skin Rabbit = 1465 mg/kg

LD50 Oral Rat = 1716 mg/kg

3-aminomethyl-3,5,5-

trimethylcyclohexylamine

a) acute toxicity

LC50 Inhalation Dust Rat > 5.01 mg/l 4h

LD50 Oral Rat = 1030 mg/kg LD50 Skin Rat > 2000 mg/kg LD50 Oral Rat = 1030 mg/kg LD50 Skin Rat > 2000 mg/kg

2-piperazin-1ylethylamine

a) acute toxicity

LD50 Skin Rabbit = 866 mg/kg

LD50 Oral Rabbit > 2097 mg/kg LD50 Skin Rabbit = 880 μ L/kg LD50 Oral Rat = 2140 μ L/kg

e) germ cell mutagenicity NOAEL Rat > 899 mg/kg

g) reproductive toxicity NOAEL Oral Rat = mg/kg

4-tert-butylphenol

a) acute toxicity

LD50 Skin Rabbit = 2318 mg/kg

LD50 Oral Rat = 4000 mg/kg

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 9 of 15

11.2 Information on other hazards

Endocrine disrupting properties:

N.A.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of components with eco-toxicological properties

List of components with eco-toxicological properties						
Component	Ident. Numb.	Ecotox Infos				
Reaction products of 3- aminomethyl-3,5,5- trimethylcyclohexylamine and 4,4' Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	3, 68609-08-5 - - EINECS: 500-	a) Aquatic acute toxicity :	LL50 Fish = mg/L 96			
		a) Aquatic acute toxicity:	NOELR Fish = 50 mg/L 96			
		a) Aquatic acute toxicity:	NOELR Daphnia = mg/L 48			
		a) Aquatic acute toxicity :	EC50 Daphnia = mg/L 48			
benzyl alcohol	CAS: 100-51-6 - EINECS: 202- 859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity :	LC50 Fish = 460 mg/L 96			
		a) Aquatic acute toxicity:	EC50 Algae = 770 mg/L 72			
		a) Aquatic acute toxicity:	EC50 Daphnia = 230 mg/L 48			
		a) Aquatic acute toxicity : EPA	LC50 Fish Pimephales promelas = 460 mg/L 96h			
2,4,6- tris(dimethylaminomethyl)phenol	CAS: 90-72-2 - EINECS: 202- 013-9 - INDEX: 603-069-00-0	a) Aquatic acute toxicity :	LC50 Fish = 175 mg/L 96h			
		a) Aquatic acute toxicity:	EC50 Algae = 46.7 mg/L 72h			
		a) Aquatic acute toxicity:	NOEC Algae = 25.1 mg/L 72h			
benzyl alcohol	CAS: 100-51-6 - EINECS: 202- 859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity :	EC50 Daphnia = 230 mg/L 48			
		a) Aquatic acute toxicity:	LC50 Fish = 770 mg/L 1			
		a) Aquatic acute toxicity:	EC50 Algae = 770 mg/L 72			
		a) Aquatic acute toxicity:	LC50 Fish = 460 mg/L 96			
		a) Aquatic acute toxicity : EPA	LC50 Fish Pimephales promelas = 460 mg/L 96h			
2-Methylpentane-1,5-diamine	CAS: 15520-10- 2 - EINECS: 239-556-6	a) Aquatic acute toxicity :	EC50 Algae > 100 mg/L 72			
		a) Aquatic acute toxicity:	EC50 Fish = 1825 mg/L 96			
		a) Aquatic acute toxicity :	EC50 Daphnia = 19.8 mg/L 48			
triethylenetetramine	CAS: 90640-67- 8, 112-24-3 - EINECS: 292- 588-2	a) Aquatic acute toxicity :	EC50 Daphnia = 31.1 mg/L 48h			
3-aminomethyl-3,5,5- trimethylcyclohexylamine	CAS: 2855-13-2 - EINECS: 220- 666-8 - INDEX: 612-067-00-9	a) Aquatic acute toxicity :	LC50 Fish = 110 mg/L 96			

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 10of 15

a) Aquatic acute toxicity: EC50 Daphnia = 23 mg/L 48

a) Aquatic acute toxicity: EC50 Daphnia = 388 mg/L 48

a) Aquatic acute toxicity: EC50 Algae > 50 mg/L 72

b) Aquatic chronic toxicity: NOEC Daphnia = 3 mg/L - 21 d

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna 14.6 mg/L 48h EPA a) Aquatic acute toxicity: EC50 Algae Desmodesmus subspicatus = 37 mg/L

72h IUCLID

2-piperazin-1-ylethylamine CAS: 140-31-8 - a) Aquatic acute toxicity: LC50 Fish = 2190 mg/L 96

EINECS: 205-411-0 - INDEX: 612-105-00-4

> a) Aquatic acute toxicity: EC50 Daphnia = 58 mg/L 48 a) Aquatic acute toxicity: EC50 Algae > 1000 mg/L 72

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 1950 mg/L 96h EPA

a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata > 1000 mg/L 96h

IUCLID

a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss >= 100 mg/L 96h

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 32 mg/L 48h

IUCLID

a) Aquatic acute toxicity: EC50 Algae Pseudokirchneriella subcapitata = 495

mg/L 72h IUCLID

4-tert-butylphenol CAS: 98-54-4 -

EINECS: 202-679-0 - INDEX: 604-090-00-8

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 4.71 mg/L 96h EPA

a) Aquatic acute toxicity: LC50 Fish Cyprinus carpio = 6.9 mg/L 96h EPA a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 3.9 mg/L 48h

IUCLID

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna 3.4 mg/L 48h EPA

a) Aquatic acute toxicity: EC50 Algae Desmodesmus subspicatus = 11.2 mg/L

72h IUCLID

12.2. Persistence and degradability

Persitence/Degradability: **Duration** Component Value Notes Reaction products of 3-Non-readily biodegradable Oxygen consumption 28 d apparent toxicity or aminomethyl-3,5,5inhibition of the micro trimethylcyclohexylamine and 4,4'inoculum

Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane

12.3. Bioaccumulative potential

Bioaccumulation Component Test Value Notes Reaction products of 3-Not bioaccumulative BCF - Bioconcentrantion

aminomethyl-3,5,5trimethylcyclohexylamine and 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-

factor

2,3-epoxypropane

Kow - Partition coefficient 3.600 log Pow 25°C, pH 7

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

PBT, vPvB or endocrine disruptor substances present in concentration >= 0,1%:

Component Ident. Numb. Quantity **Properties:**

CAS: 98-54-4 - EINECS: 202-679-0 - 67-548-EC: >=1 - <2.5 % SVHC - Endocrine disruptor 4-tert-

604-090-00-8 butylphenol

Print date 23/07/2022 **Production Name** MAPEPROOF ESM parte B Page n. 11of 15

12.6 Endocrine disrupting properties

NΙΔ

12.7 Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

14.1. UN number or ID number

2735

14.2. UN proper shipping name

ADR-Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - cycloaliphatic polyamines) IATA-Technical name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - cycloaliphatic polyamines) IMDG-Technical name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - cycloaliphatic polyamines)

14.3. Transport hazard class(es)

ADR-Class: 8
IATA-Class: 8
IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II IATA-Packing group: II IMDG-Packing group: II

14.5. Environmental hazards

Marine pollutant: No Environmental Pollutant: No IMDG-EMS: F-A, S-B

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 8

ADR-Hazard identification number: 80

ADR-Special Provisions: 274

ADR-Transport category (Tunnel restriction code): 2 (E)

Air (IATA):

IATA-Passenger Aircraft: 851 IATA-Cargo Aircraft: 855

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 12of 15

IATA-Special Provisioning: A3 A803

Sea (IMDG):

IMDG-Stowage Code: Category A IMDG-Stowage Note: SG35 IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274

IMDG-EMS: F-A, S-B

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 45 (A+B) g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

SVHC Substances:

Substances in candidate list (Art. 59 Reg. 1907/2006, REACH):

ComponentIdent. Numb.QuantityProperties:4-tert-butylphenolCAS: 98-54-4>=1 - <2.5</td>SVHC

EINECS: 202-679-0 Endocrine disruptor

Index: 604-090-00-8

German Water Hazard Class (WGK)

Class 2: hazardous for water.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 13of 15

H317	May cause an allergic skin reaction.						
H318	Causes serious eye damage.						
H319	Causes serious eye irritation.						
H332	Harmful if inhaled.						
H335	May cause respiratory irritation.						
H361	Suspected of damaging fertility or the unbo	rn child.					
H361f	Suspected of damaging fertility.						
H372	Causes damage to organs through prolonge	ed or repeated exposure if inhaled.					
H373	May cause damage to organs through prolo	nged or repeated exposure.					
H410	Very toxic to aquatic life with long lasting e	ffects.					
H412	Harmful to aquatic life with long lasting effe	ects.					
Code	Hazard class and hazard category	Description					
	riazara ciass aria riazara category	2 00 0 1 p 0 10 11					
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3					
	- ,	•					
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3					
3.1/3/Dermal 3.1/4/Dermal	Acute Tox. 3 Acute Tox. 4	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral 3.2/1A	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Corr. 1A	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4 Skin corrosion, Category 1A					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral 3.2/1A 3.2/1B	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Corr. 1A Skin Corr. 1B	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4 Skin corrosion, Category 1A Skin corrosion, Category 1B					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral 3.2/1A 3.2/1B 3.2/1C	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Corr. 1A Skin Corr. 1B Skin Corr. 1C	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4 Skin corrosion, Category 1A Skin corrosion, Category 1B Skin corrosion, Category 1C					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral 3.2/1A 3.2/1B 3.2/1C 3.2/2	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Corr. 1A Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4 Skin corrosion, Category 1A Skin corrosion, Category 1B Skin corrosion, Category 1C Skin irritation, Category 2					
3.1/3/Dermal 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral 3.2/1A 3.2/1B 3.2/1C 3.2/2 3.3/1	Acute Tox. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Corr. 1A Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Eye Dam. 1	Acute toxicity (dermal), Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4 Skin corrosion, Category 1A Skin corrosion, Category 1B Skin corrosion, Category 1C Skin irritation, Category 2 Serious eye damage, Category 1					

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Specific target organ toxicity — single exposure, Category 3

Specific target organ toxicity — repeated exposure, Category 1

Specific target organ toxicity — repeated exposure, Category 2

Chronic (long term) aquatic hazard, category 1

Chronic (long term) aquatic hazard, category 3

(EC) Nr. 1272/2008	
3.1/4/Oral	Calculation method
3.2/1A	Calculation method
3.3/1	Calculation method
3.4.2/1	Calculation method
3.9/2	Calculation method
4.1/C3	Calculation method

Classification according to Regulation Classification procedure

Causes severe skin burns and eye damage.

Causes skin irritation.

H314 H315

3.8/3

3.9/1

3.9/2

4.1/C1

4.1/C3

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

STOT SE 3

STOT RE 1

STOT RE 2

Aquatic Chronic 1

Aquatic Chronic 3

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 14of 15

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Print date 23/07/2022 Production Name MAPEPROOF ESM parte B Page n. 15of 15